



- SPEC :
- 1.Housing:High-Temp Plastic,UL94-V
 - 2.Locker :LCP
 - 3.Contact:Phosphor Bronze
 - 4.Current Rating:0.5Amps
 - 5.Insulator Resistance:800m Ohms Max.
 - 6.Dielectric Withstanding:AC500V
 - 7.Operating Temperature:-25°C~+85°C

● : 表示現有可供應PIN數

PIN	DIM.A	DIM.B	DIM.C	DIM.D
2	9.10	3.15	1.00	7.20
3	10.10	4.15	2.00	8.20
4	11.10	5.15	3.00	9.20
5	12.10	6.15	4.00	10.20
6	13.10	7.15	5.00	11.20
7	14.10	8.15	6.00	12.20
8	15.10	9.15	7.00	13.20
9	16.10	10.15	8.00	14.20
10	17.10	11.15	9.00	15.20
11	18.10	12.15	10.00	16.20
12	19.10	13.15	11.00	17.20
13	20.10	14.15	12.00	18.20
14	21.10	15.15	13.00	19.20
15	22.10	16.15	14.00	20.20
16	23.10	17.15	15.00	21.20
17	24.10	18.15	16.00	22.20
18	25.10	19.15	17.00	23.20
19	26.10	20.15	18.00	24.20
20	27.10	21.15	19.00	25.20
21	28.10	22.15	20.00	26.20
22	29.10	23.15	21.00	27.20
23	30.10	24.15	22.00	28.20
24	31.10	25.15	23.00	29.20
25	32.10	26.15	24.00	30.20
26	33.10	27.15	25.00	31.20
27	34.10	28.15	26.00	32.20
28	35.10	29.15	27.00	33.20
29	36.10	30.15	28.00	34.20
30	37.10	31.15	29.00	35.20
31	38.10	32.15	30.00	36.20
32	39.10	33.15	31.00	37.20
33	40.10	34.15	32.00	38.20
34	41.10	35.15	33.00	39.20
35	42.10	36.15	34.00	40.20

ORDERING INFORMATION:

FPCL - 10550 DVSP - xx - T - x - A

- PLATING: T=TIN G=GOLD FLASH
- PACKING T=TUBE
- NO. of contacts
- Series name
- PITCH=1.0mm
- FPC SERIES



鼎掄實業有限公司
DINGLUN INDUSTRIAL CO., LTD.

TITLE
FPC 1.0PH 5.5H 抽屜直插正腳位 (平面)

DRAWN:	michael lin 2013/06/18	TOLERANCE	SCALE
CHECKED:	Eddie Liu 2013/06/18	.X±0.30	None
APPROVED:	Eddie Liu 2013/06/18	.XX±0.20	UNIT
		.XXX±0.10	mm
		PROJECTION	REV.
		⊕ ⊖	A

P/N NO. FPCF 10550DVSP-xx-Tx-A
DWG. NO.
CUSTOMER P/N NO.

REV.	REASONS	DATE	DRAWN
1			
2			
3			
4			
5			