

RECOMMEND PCB LAYOUT
TOLERANCE: 0.05


SPEC :

- Housing: High-Temp Plastic, UL94-V
Color: Nature
- Locker: High-Temp Plastic, UL94-V
Color: Coffee
- Contact: Phosphor Bronze
Initial: 30m Ohms Max.
Voltage Rating: 50V AC, DC
- Solder Tab: BRASS
- Temperature Rating: -25°C ~ +85°C
- Dielectric Withstanding Voltage: 500V AC/Min

● : 表示現有提供PIN數

	PIN	DDIM.A	DIM.B	DIM.C	DIM.D
	30	37.00	31.08	29.00	35.05
	31	38.00	32.08	30.00	36.05
	32	39.00	33.08	31.00	37.05
	33	40.00	34.08	32.00	38.05
	34	41.00	35.08	33.00	39.05
	35	42.00	36.08	34.00	40.05
	36	43.00	37.08	35.00	41.05
	37	44.00	38.08	36.00	42.05
	38	45.00	39.08	37.00	43.05
	39	46.00	40.08	38.00	44.05
	40	47.00	41.08	39.00	45.05

ORDERING INFORMATION:



- PLATING: T=TIN G=GOLD FLASH
- PACKING T=TUBE R=REEL
- NO. of contacts
- Series name
- PITCH=1.0mm
- FPC SERIES

RECOMMEND PCB LAYOUT
TOLERANCE: ±0.05



TITLE
FPC 1.0PH 2.5H 抽屜式上接

DRAWN: *michael lin*
2017/07/22

TOLERANCE
.X±0.30

SCALE
None

P/N NO.
FPCZ-10250DHUE-xx-xx

CHECKED: *Eddie Liu*
2017/07/22

UNIT
.XX±0.20
.XXX±0.10

DWG. NO.

APPROVED: *Eddie Liu*
2017/07/23

PROJECTION
REV. A

CUSTOMER P/N NO.

REV.	REASONS	DATE	DRAWN

1	2	3	4	5	6	7	8	9
---	---	---	---	---	---	---	---	---